



2025 TYRE CATALOGUE

Passenger Car and SUV



CRUZE

» Company Profile

AUTOCRUZE: Where Innovation Meets the Open Road

At Autocruze, we engineer revolutions in motion - where advanced technology dances with the rhythm of the road.

Born from the fusion of biomimetic design and quantum material science, our tires are silent revolutionaries beneath every vehicle. More than rubber meeting asphalt, they're adaptive ecosystems that transform mundane drives into symphonies of precision engineering.

Within our Industry 4.0 plant:

- ✓ 40-million unit annual capacity
- ✓ AI-driven quality control with micron-level accuracy
- ✓ Closed-loop sustainable manufacturing system
- ✓ Strategic OEM partner to global automotive leaders

AUTOCRUZE: Your Journey, Perfected.



SUMMER



CATCHFORS PCR



CATCHFORS UHP

SUMMER

 **AUTOCRUZE**

UTQG: 480 A A(B)

ECO PCR
Eco-Friendly with low rolling resistance, long life and good breaking performance tire for passenger cars.

RANGE: 12-16 ASPECT RATIO: 50-80
SPEED RATE: H/T/V SECTION WIDTH: 145-235

CATCHFORS
PCR



CATCHFORS PCR



Four wide circumferential tread grooves and lateral grooves with fine sipes provide efficient water evacuation, outstanding wet performance.



Continuous outside tread blocks enhance excellent performance and precise control when cornering at high speed. The special rib segment design optimize contact pressure distribution, improve road contact area and provide precise control. The serrated groove walls absorb noise and deliver a quieter ride.



The 3D "F" blade groove tread blocks with variable pitch design reduce road slapping noise and lower resonance noise.



Special tread compound delivers excellent grip on both dry and wet roads and reduce the rolling resistance to save oil and protect environment.



Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
12	145/70R12 69T	BLK	4.5	150	509	300/44	✓
	155/70R12 73T	BLK	4.5	157	523	300/44	✓
	165/70R12 77T	BLK	5.0	170	537	300/44	✓
	175/70R12 80T	BLK	5.0	177	551	300/44	✓
13	155/65R13 73T	BLK	5.0	157	532	300/44	✓
	155/70R13 75T	BLK	4.5	157	548	300/44	✓
	155/80R13 79T	BLK	4.5	157	578	300/44	✓
	165/65R13 77T	BLK	5.0	170	544	300/44	✓
	165/70R13 79T	BLK	5.0	170	562	300/44	✓
	165/80R13 83T	BLK	4.5	165	594	300/44	✓
	175/60R13 77H	BLK	5.0	177	540	300/44	✓
	175/70R13 82T	BLK	5.0	177	576	300/44	✓
	185/60R13 80H	BLK	5.0	189	552	300/44	✓
	185/70R13 86T	BLK	5.5	189	590	300/44	✓
14	155/65R14 75H	BLK	4.5	154	557	300/44	✓
	165/60R14 75H	BLK	5.0	170	554	300/44	✓
	165/60R14 79TXL	BLK	5.0	170	554	340/50	✓
	165/65R14 79H	BLK	5.0	170	570	300/44	✓
	165/70R14 81H	BLK	5.0	170	588	300/44	✓
	165/70R14 85TXL	BLK	5.0	170	588	340/50	✓
	175/65R14 82H	BLK	5.0	177	584	300/44	✓
	175/65R14 86TXL	BLK	5.0	177	584	340/50	✓
	175/70R14 84H	BLK	5.0	177	602	300/44	✓
	175/70R14 88TXL	BLK	5.0	177	602	340/50	✓
	185/50R14 77V	BLK	6.0	194	542	300/44	✓
	185/55R14 80H	BLK	6.0	194	560	300/44	✓
	185/60R14 82H	BLK	5.5	189	578	300/44	✓
	185/65R14 86H	BLK	5.5	189	596	300/44	✓
	185/70R14 88H	BLK	5.5	189	616	300/44	✓
	195/60R14 86H	BLK	6.0	201	590	300/44	✓
	195/65R14 89H	BLK	6.0	201	610	300/44	✓
	195/70R14 91H	BLK	6.0	201	630	300/44	✓
	205/60R14 88H	BLK	6.0	209	602	300/44	✓
	205/70R14 95H	BLK	6.0	209	644	300/44	✓

Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
15	145/65R15 72T	BLK	4.5	150	569	300/44	✓
	155/60R15 74T	BLK	5.0	157	567	300/44	✓
	165/60R15 77H	BLK	5.0	170	579	300/44	✓
	165/65R15 81H	BLK	5.0	170	595	300/44	✓
	175/55R15 77H	BLK	5.5	182	573	300/44	✓
	175/60R15 81H	BLK	5.0	177	591	300/44	✓
	175/65R15 84H	BLK	5.0	177	609	300/44	✓
	185/55R15 82V	BLK	6.0	194	585	300/44	✓
	185/60R15 84H	BLK	5.5	189	603	300/44	✓
	185/60R15 88HXL	BLK	5.5	189	603	340/50	✓
	185/65R15 88H	BLK	5.5	189	621	300/44	✓
	185/65R15 92TXL	BLK	5.5	189	621	340/50	✓
	195/60R15 88H	BLK	6.0	201	615	300/44	✓
	195/60R15 88V	BLK	6.0	201	615	300/44	✓
	195/65R15 91V	BLK	6.0	201	635	300/44	✓
	195/65R15 95HXL	BLK	6.0	201	635	340/50	✓
	205/60R15 91V	BLK	6.0	209	627	300/44	✓
	205/65R15 94H	BLK	6.0	209	647	300/44	✓
	205/65R15 94V	BLK	6.0	209	647	300/44	✓
	205/70R15 96H	BLK	6.0	209	669	300/44	✓
	215/65R15 96H	BLK	6.5	221	661	300/44	✓
	215/65R15 100HXL	BLK	6.5	221	661	340/50	✓
	215/70R15 98H	BLK	6.5	221	683	300/44	✓
	225/70R15 100H	BLK	6.5	228	697	300/44	✓
16	175/50R16 77V	BLK	5.5	182	582	300/44	✓
	185/50R16 81V	BLK	6.0	194	592	300/44	✓
	185/55R16 83H	BLK	6.0	194	610	300/44	✓
	195/60R16 89H	BLK	6.0	201	641	300/44	✓
	205/55R16 91V	BLK	6.5	214	632	300/44	✓
	205/60R16 92V	BLK	6.0	209	652	300/44	✓
	205/60R16 96HXL	BLK	6.0	209	652	340/50	✓
	205/65R16 95H	BLK	6.0	209	672	300/44	✓
	215/60R16 95V	BLK	6.5	221	664	300/44	✓
	215/60R16 99HXL	BLK	6.5	221	664	340/50	✓
	215/65R16 98H	BLK	6.5	221	686	300/44	✓
	215/65R16 102HXL	BLK	6.5	221	686	340/50	✓
	225/60R16 98H	BLK	6.5	228	676	300/44	✓
	225/60R16 102HXL	BLK	6.5	228	676	340/50	✓
	225/65R16 100H	BLK	6.5	228	698	300/44	✓
	235/60R16 100H	BLK	7.0	240	688	300/44	✓



UTQG: 420 A A

SPORTY PERFORMANCE PCR

Ultra high performance tire provides ultimate performance during high speed drive.

RANGE: 15-21

ASPECT RATIO: 30-60

SPEED RATE: V/W

SECTION WIDTH: 185-315

CATCHFORS
UHP



CATCHFORS UHP



Four wide circumferential tread grooves and lateral grooves with fine sipes provide efficient water evacuation, outstanding wet performance.



The unique ribbed tread pattern design optimizes pressure distribution and increases the contact area; the intermittent rubber strip design disrupts resonance, effectively reducing noise for a quiet and comfortable ride.



Asymmetric tread pattern design, combined with an adaptive tread design specifically engineered for sport-oriented ultra-high performance, ensures exceptional stability and riding comfort even on both wet and dry road surfaces.



Special tread compound delivers excellent grip on both dry and wet roads and reduce the rolling resistance to save oil and protect environment.



Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
15	195/45R15 82VXL	BLK	4.5	150	509	340/50	✓
	195/50R15 82V	BLK	6.0	201	577	300/44	✓
	195/55R15 85V	BLK	6.0	201	595	300/44	✓
	205/50R15 86V	BLK	5.0	177	551	300/44	✓
16	185/55R16 87VXL	BLK	5.0	157	532	340/50	✓
	195/45R16 84VXL	BLK	4.5	157	548	340/50	✓
	195/50R16 88VXL	BLK	6.0	201	602	340/50	✓
	195/55R16 91VXL	BLK	5.0	170	544	340/50	✓
	205/45ZR16 87WXL	BLK	5.0	170	562	340/50	✓
	205/50ZR16 91WXL	BLK	4.5	165	594	340/50	✓
	205/55ZR16 94WXL	BLK	5.0	177	540	340/50	✓
	215/40ZR16 86WXL	BLK	5.0	177	576	340/50	✓
	215/45ZR16 90WXL	BLK	5.0	189	552	340/50	✓
	215/55ZR16 97WXL	BLK	5.5	189	590	340/50	✓
	225/50ZR16 96WXL	BLK	4.5	154	557	340/50	✓
	225/55ZR16 99WXL	BLK	5.0	170	554	340/50	✓
	195/40ZR17 81WXL	BLK	5.0	170	554	340/50	✓
17	195/45ZR17 85WXL	BLK	5.0	170	570	340/50	✓
	205/40ZR17 84WXL	BLK	5.0	170	588	340/50	✓
	205/45ZR17 88WXL	BLK	5.0	170	588	340/50	✓
	205/50ZR17 93WXL	BLK	5.0	177	584	340/50	✓
	205/55ZR17 95WXL	BLK	5.0	177	584	340/50	✓
	215/45ZR17 91WXL	BLK	5.0	177	602	340/50	✓
	215/50ZR17 95WXL	BLK	5.0	177	602	340/50	✓
	215/55ZR17 98WXL	BLK	6.0	194	542	340/50	✓
	225/45ZR17 94WXL	BLK	6.0	194	560	340/50	✓
	225/50ZR17 98WXL	BLK	5.5	189	578	340/50	✓
	225/55ZR17 101WXL	BLK	5.5	189	596	340/50	✓
	235/45ZR17 97WXL	BLK	5.5	189	616	340/50	✓
	235/50ZR17 100WXL	BLK	6.0	201	590	340/50	✓
	235/55ZR17 103WXL	BLK	6.0	201	610	340/50	✓
	245/40ZR17 95WXL	BLK	6.0	201	630	340/50	✓
	245/45ZR17 99WXL	BLK	6.0	209	602	340/50	✓
	255/40ZR17 98WXL	BLK	9.0	260	636	340/50	✓

Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
18	215/35ZR18 84WXL	BLK	7.5	218	607	340/50	✓
	215/40ZR18 89WXL	BLK	7.5	218	629	340/50	✓
	215/45ZR18 93WXL	BLK	7.5	213	650	340/50	✓
	215/55ZR18 99WXL	BLK	7.0	226	693	340/50	✓
	225/40ZR18 92WXL	BLK	8.0	230	637	340/50	✓
	225/45ZR18 95WXL	BLK	7.5	225	659	340/50	✓
	225/50ZR18 99WXL	BLK	7.5	228	683	340/50	✓
	225/55ZR18 102WXL	BLK	7.0	233	705	340/50	✓
	235/40ZR18 95WXL	BLK	8.5	241	645	340/50	✓
	235/45ZR18 98WXL	BLK	8.0	240	667	340/50	✓
	235/50ZR18 101WXL	BLK	7.5	243	693	340/50	✓
	235/55ZR18 104WXL	BLK	7.5	245	715	340/50	✓
	245/40ZR18 97WXL	BLK	8.5	248	653	340/50	✓
	245/45ZR18 100WXL	BLK	8.0	243	677	340/50	✓
	255/35ZR18 94WXL	BLK	9.0	260	635	340/50	✓
	255/40ZR18 99WXL	BLK	9.0	263	661	340/50	✓
	255/45ZR18 103WXL	BLK	8.5	257	687	340/50	✓
	255/55ZR18 109WXL	BLK	8.0	265	737	340/50	✓
	265/35ZR18 97WXL	BLK	8.0	271	643	340/50	✓
	275/35ZR18 99WXL	BLK	9.5	278	650	340/50	✓
19	215/35ZR19 85WXL	BLK	7.5	221	634	340/50	✓
	225/35ZR19 88WXL	BLK	8.0	230	641	340/50	✓
	225/40ZR19 93WXL	BLK	8.0	230	663	340/50	✓
	225/45ZR19 96WXL	BLK	7.5	225	685	340/50	✓
	225/55ZR19 103WXL	BLK	7.0	233	732	340/50	✓
	235/35ZR19 91WXL	BLK	8.5	241	647	340/50	✓
	235/40ZR19 96WXL	BLK	8.5	241	671	340/50	✓
	235/45ZR19 99WXL	BLK	8.0	236	695	340/50	✓
	235/50ZR19 103WXL	BLK	7.5	245	719	340/50	✓
	235/55ZR19 105WXL	BLK	7.5	245	741	340/50	✓
	245/35ZR19 93WXL	BLK	8.5	248	655	340/50	✓
	245/40ZR19 98WXL	BLK	8.5	248	679	340/50	✓
	245/45ZR19 102WXL	BLK	8.0	243	703	340/50	✓
	245/55ZR19 107WXL	BLK	7.5	253	753	340/50	✓
	255/30ZR19 91WXL	BLK	9.0	260	637	340/50	✓
	255/35ZR19 96WXL	BLK	9.0	260	661	340/50	✓
	255/40ZR19 100WXL	BLK	9.0	260	687	340/50	✓
	255/45ZR19 104WXL	BLK	8.5	255	715	340/50	✓
	255/50ZR19 107WXL	BLK	8.0	265	739	340/50	✓
	255/55ZR19 111WXL	BLK	8.0	265	763	340/50	✓
	265/30ZR19 93WXL	BLK	9.5	271	643	340/50	✓
	265/50ZR19 110WXL	BLK	8.5	277	749	340/50	✓
	275/30ZR19 96WXL	BLK	9.5	278	649	340/50	✓
	275/35ZR19 100WXL	BLK	9.5	278	675	340/50	✓
	275/40ZR19 105WXL	BLK	9.5	278	703	340/50	✓
	275/45ZR19 108WXL	BLK	9.0	278	730	340/50	✓
	275/55ZR19 111W	BLK	8.5	280	787	300/44	✓
	285/45ZR19 111WXL	BLK	9.5	285	737	340/50	✓
20	225/35ZR20 93WXL	BLK	8.0	230	644	340/50	✓
	235/30ZR20 88WXL	BLK	8.5	242	650	340/50	✓
	235/55ZR20 105WXL	BLK	7.5	245	766	340/50	✓
	245/30ZR20 97WXL	BLK	8.5	247	657	340/50	✓
	245/35ZR20 95WXL	BLK	8.5	248	680	340/50	✓
	245/40ZR20 99WXL	BLK	8.5	248	704	340/50	✓
	245/45ZR20 103WXL	BLK	8.0	243	728	340/50	✓
	255/30ZR20 92WXL	BLK	9.0	260	662	340/50	✓
	255/35ZR20 97WXL	BLK	9.0	260	686	340/50	✓
	255/45ZR20 105WXL	BLK	8.5	255	738	340/50	✓
	255/50ZR20 109WXL	BLK	8.0	265	764	340/50	✓
	255/55ZR20 110WXL	BLK	8.0	260	789	340/50	✓
	265/45ZR20 108WXL	BLK	9.0	266	746	340/50	✓
	265/50ZR20 111WXL	BLK	9.0	277	774	340/50	✓

Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
20	275/30ZR20 97WXL	BLK	9.5	278	674	340/50	✓
	275/35ZR20 102WXL	BLK	9.5	278	700	340/50	✓
	275/40ZR20 106WXL	BLK	9.5	278	728	340/50	✓
	275/45ZR20 110WXL	BLK	9.0	273	756	340/50	✓
	275/50ZR20 113WXL	BLK	8.5	284	784	340/50	✓
	275/55ZR20 117WXL	BLK	8.5	284	810	340/50	✓
	275/60ZR20 119WXL	BLK	8.0	279	838	340/50	✓
	285/50ZR20 116WXL	BLK	9.0	297	794	340/50	✓
	305/40ZR20 112WXL	BLK	11.0	313	752	340/50	✓
	315/35ZR20 110WXL	BLK	11.0	320	728	340/50	✓
21	245/35ZR21 96WXL	BLK	8.5	245	705	340/50	✓
	275/30ZR21 98WXL	BLK	9.5	278	698	340/50	✓
	275/40ZR21 107WXL	BLK	9.5	278	753	340/50	✓
	275/45ZR21 110WXL	BLK	9.5	278	780	340/50	✓
	295/35ZR21 107WXL	BLK	10.5	301	739	340/50	✓
	295/40ZR21 111WXL	BLK	10.5	301	769	340/50	✓
	315/35ZR21 111WXL	BLK	11.0	320	753	340/50	✓
	315/40ZR21 115WXL	BLK	11.0	323	784	340/50	✓



4X4



4X4

AUTOCRUZE



CATCHFORS H/T



CATCHFORS AT II

UTQG: 500 A A

CITY SUV

RANGE: 16-18 ASPECT RATIO: 55-70
SPEED RATE: H/V SECTION WIDTH: 215-285

CATCHFORS
H/T



CATCHFORS H/T



Four wide circumferential tread grooves deliver the ride stability and offer excellent performance on wet conditions. Improved grooves and bead profile design offer better ride stability, endurance and handling performance.



The open shoulder grooves prevent aquaplaning with enhanced wet grip performance and provide excellent water evacuation. Continuous tread blocks on both shoulder give great support to enhance the ride stability when cornering.



Variable pitch pattern and solid center ribs improve the ride stability, reduce the noise and deliver a comfortable ride.



High-density sipes with special compound deliver a smooth ride and improve traction on dry and wet roads. Jointless Nylon band and strong structure design provided the strong carcass to enhance the reliability and durability.



Wheel Diameter	Size Description		Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
16	215/70R16	100H	BLK	6.5	221	708	300/44	✓
	225/70R16	107HXL	BLK	6.5	228	722	340/50	✓
	235/70R16	106H	BLK	7.0	240	736	300/44	✓
	245/70R16	111HXL	BLK	7.0	248	750	340/50	✓
	255/65R16	109H	BLK	7.5	262	737	300/44	✓
	255/70R16	111H	BLK	7.5	260	764	300/44	✓
	265/70R16	112H	BLK	8.0	272	778	300/44	✓
	275/70R16	114H	BLK	8.0	279	792	300/44	✓
17	215/60R17	100VXL	BLK	6.5	221	690	340/50	✓
	215/65R17	99H	BLK	6.5	221	710	300/44	✓
	225/60R17	103VXL	BLK	6.5	228	702	340/50	✓
	225/65R17	102H	BLK	6.5	228	724	300/44	✓
	235/60R17	106VXL	BLK	7.0	240	714	340/50	✓
	235/65R17	108HXL	BLK	7.0	240	738	340/50	✓
	245/65R17	111HXL	BLK	7.0	248	750	340/50	✓
	245/70R17	110H	BLK	7.0	248	776	300/44	✓
	255/60R17	110VXL	BLK	7.5	260	738	340/50	✓
	255/65R17	110H	BLK	7.5	260	764	300/44	✓
	265/65R17	112H	BLK	8.0	272	776	300/44	✓
	265/70R17	115H	BLK	8.0	272	804	300/44	✓
	275/65R17	115H	BLK	8.0	279	791	300/44	✓
	285/65R17	116H	BLK	8.5	292	802	300/44	✓
18	225/60R18	104VXL	BLK	6.5	228	727	340/50	✓
	235/60R18	107VXL	BLK	7.0	240	739	340/50	✓
	235/65R18	110HXL	BLK	7.0	240	763	340/50	✓
	245/60R18	105H	BLK	7.0	248	751	300/44	✓
	255/55R18	109VXL	BLK	8.0	265	737	340/50	✓
	255/60R18	112VXL	BLK	7.5	257	763	340/50	✓
	255/70R18	113H	BLK	7.5	260	815	300/44	✓
	265/60R18	110H	BLK	8.0	272	775	300/44	✓
	265/65R18	114H	BLK	8.0	272	801	300/44	✓
	265/70R18	116H	BLK	8.0	272	827	300/44	✓
	275/65R18	116H	BLK	8.0	279	815	300/44	✓
	285/60R18	120HXL	BLK	8.5	290	802	340/50	✓



UTQG: 500 A B

Only for P series

ALL TERRAIN

RANGE: 15-20

ASPECT RATIO: 50-85

SPEED RATE: H/R/S/T

SECTION WIDTH: 215-325

CATCHFORS AT II



CATCHFORS AT II



Four main zigzag grooves and rough lateral blocks provide excellent traction on all kinds of road conditions.



The open shoulder grooves prevent aquaplaning with enhanced wet grip performance and provide excellent water evacuation. The white letter styling provide a artistic image.



The block tread design with multiple sipes provide outstanding off-road traction and reduce tread damage on off-road condition.



Jointless Nylon band and strong structure design provided the strong carcass to enhance the reliability and durability. Special tread compound and wide footprint enhance tread life and deliver excellent braking on wet and dry roads.



Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
15	LT215/75R15 C 100/97R	RWL	6.0	216	703	340/50	✓
	LT235/75R15 C 104/101R	RWL	6.5	235	733	340/50	✓
16	LT215/85R16 E 115/112R	RWL	6.0	216	772	550/80	✓
	LT225/75R16 E 115/112R	RWL	6.0	223	744	550/80	✓
	LT235/85R16 E 120/116R	RWL	6.5	235	806	550/80	✓
	LT245/70R16 D 113/110S	RWL	7.0	248	750	450/65	✓
	LT245/75R16 E 120/116R	RWL	7.0	248	774	550/80	✓
	LT265/70R16 E 121/118R	RWL	8.0	272	778	550/80	✓
	LT265/75R16 E 123/120R	RWL	7.5	267	804	550/80	✓
	LT285/75R16 E 126/123R	RWL	8.0	286	834	550/80	✓
	LT305/70R16 E 124/121R	RWL	9.0	310	838	550/80	✓
	LT315/75R16 E 127/124R	RWL	8.5	326	886	550/80	✓
17	LT245/65R17 D 111/108S	RWL	7.0	248	750	450/65	✓
	LT245/70R17 E 119/116R	RWL	7.0	248	776	550/80	✓
	LT245/75R17 E 121/118R	RWL	7.0	248	800	550/80	✓
	LT265/65R17 E 120/117S	RWL	7.0	272	776	550/80	✓
	LT265/70R17 E 121/118R	RWL	8.0	272	804	550/80	✓
	LT285/70R17 E 121/118R	RWL	8.5	284	831	550/80	✓
18	LT265/60R18 E 119/116S	RWL	8.0	272	775	550/80	✓
	LT265/65R18 E 122/119R	RWL	8.0	272	801	550/80	✓
	LT275/65R18 E 123/120R	RWL	8.0	279	813	550/80	✓
	LT275/70R18 E 125/122R	RWL	8.0	279	843	550/80	✓
20	LT265/60R20 E 121/118S	RWL	8.0	272	826	550/80	✓
	LT275/55R20 E 120/117S	RWL	8.5	284	810	550/80	✓
	LT275/60R20 E 123/120S	RWL	8.0	279	836	550/80	✓
	LT275/65R20 E 126/123R	RWL	8.0	279	866	550/80	✓
15	31X10.50R15LT C 109S	RWL	8.5	268	775	350/51	✓
	32X11.50R15LT C 113R	RWL	9.0	292	813	350/51	✓
	33X12.50R15LT C 108R	RWL	10.0	320	838	350/51	✓
	35X12.50R15LT C 113R	RWL	10.0	326	890	350/51	✓
17	33X12.50R17LT D 120R	RWL	10.0	320	838	450/65	✓
	35X12.50R17LT D 121R	RWL	10.0	326	890	450/65	✓
18	33X12.50R18LT E 118R	RWL	10.0	320	838	550/80	✓
	35X12.50R18LT E 123R	RWL	10.0	320	890	550/80	✓

Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
16	P265/70R16 112T	RWL	8.0	272	778	300/44	✓
	P265/75R16 116T	RWL	7.5	267	804	300/44	✓
17	P265/65R17 112T	RWL	7.0	272	776	300/44	✓
	P265/70R17 115T	RWL	8.0	272	804	300/44	✓
18	P265/60R18 114TXL	RWL	8.0	272	775	340/50	✓
	P265/65R18 116TXL	RWL	8.0	272	801	340/50	✓
20	P265/50R20 111HXL	RWL	9.0	277	774	340/50	✓
	P265/55R20 115HXL	RWL	8.5	274	800	340/50	✓
	P275/55R20 117TXL	RWL	8.5	284	810	340/50	✓
	P275/60R20 119TXL	RWL	8.0	279	836	340/50	✓

*Note:

Load Range	Ply
C	6PR
D	8PR
E	10PR



WINTER



SNOWBLAZER



SNOWBLAZER UHP



SNOWBLAZER MAX

WINTER

 **AUTOCRUZE**

WINTER TIRE

Ultimate winter tire,optimum grip performance.

RANGE: 13-18 ASPECT RATIO: 50-80
SPEED RATE: H/R/T SECTION WIDTH: 155-275

SNOWBLAZER



SNOWBLAZER



Central across & 2 wide straight circumferential grooves, with the design of convexes in the bottom, improve the traction, shorten braking distance and increase the stability on the snow road.



Bionic tread pattern design makes rge whole tread blocks' stiffness more logocal, with the optimized deployment of "V" shape sipes, provide great grip on snow & ice conditions.



Wide rolling tread, by using computer-optimized design, make sure enough contact area for more grip. The wide open shoulder grooves prevent aquaplaning with enhanced wet grip and provide excellent water & snow evacuation.



Special tread compound remains flexible at lower temperatures to make sure the grip on winter road conditions and reduce the rolling resistance.



Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
13	155/70R13 75T	BLK	4.5	157	548	300/44	✓
	155/80R13 79T	BLK	4.5	157	578	300/44	✓
	165/70R13 79T	BLK	5.0	170	562	300/44	✓
	175/70R13 82T	BLK	5.0	177	576	300/44	✓
14	155/65R14 75T	BLK	4.5	154	557	300/44	✓
	165/60R14 75T	BLK	5.0	170	554	300/44	✓
	165/60R14 79TXL	BLK	5.0	170	554	340/50	✓
	165/65R14 79T	BLK	5.0	170	570	300/44	✓
	165/70R14 81T	BLK	5.0	170	588	300/44	✓
	165/70R14 85TXL	BLK	5.0	170	588	340/50	✓
	175/65R14 82T	BLK	5.0	177	584	300/44	✓
	175/65R14 86TXL	BLK	5.0	177	584	340/50	✓
	175/70R14 84T	BLK	5.0	177	602	300/44	✓
	175/70R14 88TXL	BLK	5.0	177	602	340/50	✓
	185/60R14 82T	BLK	5.5	189	578	300/44	✓
	185/65R14 86T	BLK	5.5	189	596	300/44	✓
	185/70R14 92TXL	BLK	5.5	189	616	340/50	✓
	195/70R14 95TXL	BLK	6.0	201	630	340/50	✓
15	155/60R15 74T	BLK	5.0	157	567	300/44	✓
	165/60R15 81TXL	BLK	5.0	170	579	340/50	✓
	165/65R15 81T	BLK	5.0	170	595	300/44	✓
	175/55R15 77T	BLK	5.5	182	573	300/44	✓
	175/60R15 81T	BLK	5.0	177	591	300/44	✓
	175/65R15 84T	BLK	5.0	177	609	300/44	✓
	185/55R15 82H	BLK	6.0	194	585	300/44	✓
	185/60R15 84H	BLK	5.5	189	603	300/44	✓
	185/60R15 88HXL	BLK	5.5	189	603	340/50	✓
	185/65R15 88H	BLK	5.5	189	621	300/44	✓
	185/65R15 92TXL	BLK	5.5	189	621	340/50	✓
	195/50R15 82H	BLK	6.0	201	577	300/44	✓
	195/55R15 85H	BLK	6.0	201	595	300/44	✓
	195/60R15 88H	BLK	6.0	201	615	300/44	✓
	195/65R15 91H	BLK	6.0	201	635	300/44	✓
	195/65R15 95TXL	BLK	6.0	201	635	340/50	✓

Wheel Diameter	Size Description		Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
16	205/55R16	91H	BLK	6.5	214	632	300/44	✓
	205/60R16	92H	BLK	6.0	209	652	300/44	✓
	205/60R16	96HXL	BLK	6.0	209	652	340/50	✓
	215/60R16	95H	BLK	6.5	221	664	300/44	✓
	215/60R16	99HXL	BLK	6.5	221	664	340/50	✓
	215/65R16	98H	BLK	6.5	221	686	300/44	✓
	215/65R16	102HXL	BLK	6.5	221	686	340/50	✓
	215/70R16	100T	BLK	6.5	217	708	300/44	✓
	225/60R16	98H	BLK	6.5	228	676	300/44	✓
	225/60R16	102HXL	BLK	6.5	228	676	340/50	✓
	225/65R16	100H	BLK	6.5	228	698	300/44	✓
	235/65R16	103H	BLK	7.0	240	712	300/44	✓
	225/70R16	107TXL	BLK	6.5	228	722	340/50	✓
	235/70R16	106T	BLK	7.0	240	736	300/44	✓
	245/70R16	111TXL	BLK	7.0	248	750	340/50	✓
	265/70R16	112T	BLK	8.0	272	778	300/44	✓
17	215/60R17	96H	BLK	6.5	221	690	300/44	✓
	215/65R17	99H	BLK	6.5	221	710	300/44	✓
	225/60R17	99H	BLK	6.5	228	702	300/44	✓
	225/65R17	102T	BLK	6.5	228	724	300/44	✓
	235/65R17	108TXL	BLK	7.0	240	738	340/50	✓
	245/65R17	111TXL	BLK	7.0	248	750	340/50	✓
	265/65R17	112T	BLK	8.0	272	776	300/44	✓
	265/70R17	115T	BLK	8.0	272	804	300/44	✓
16	LT225/75R16	E 115/112R	BLK	6.0	223	744	550/80	✓
	LT245/75R16	E 120/116R	BLK	7.0	248	774	550/80	✓
17	LT245/70R17	E 119/116R	BLK	7.0	248	782	550/80	✓
	LT265/70R17	E 121/118R	BLK	8.0	272	804	550/80	✓
18	LT275/65R18	E 123/120R	BLK	8.0	279	813	550/80	✓
	LT275/70R18	E 125/122R	BLK	8.0	279	843	550/80	✓



WINTER
PERFORMANCE PCR

Extreme winter tyres,suv's best partner.

RANGE: 16-20 ASPECT RATIO: 35-60
SPEED RATE: H/V SECTION WIDTH: 185-315

SNOWBLAZER
UHP



SNOWBLAZER UHP



Four wide circumferential tread grooves and lateral grooves with fine sipes provide efficient water evacuation, outstanding wet performance.



Continuous outside tread blocks enhance excellent performance and precise control when cornering at high speed. The special rib segment design optimize contact pressure distribution, improve road contact area and provide precise contro.



Utilizing AI computer-simulated optimized wide-area rolling contact surface design for precise ground pressure distribution control. The innovative shoulder drainage network system effectively blocks water film formation, providing superior wet surface adhesion with efficient snow evacuation capabilities.



Special tread compound remains flexible at lower temperatures to make sure the grip on winter road conditions and reduce the rolling resistance.



Wheel Diameter	Size Description		Sidewall	Standard Rim	Section Width (mm)	OA Diameter (mm)	Max. Pressure (kpa/psi)	M+S
16	185/50R16	81H	BLK	6.0	194	592	300/44	✓
	185/55R16	87HXL	BLK	6.0	194	610	340/50	✓
	195/45R16	84HXL	BLK	6.5	195	582	340/50	✓
	195/50R16	88HXL	BLK	6.0	201	603	340/50	✓
	195/55R16	91HXL	BLK	6.0	190	619	340/50	✓
	205/55R16	94HXL	BLK	6.5	214	632	340/50	✓
	215/55R16	97HXL	BLK	7.0	226	642	340/50	✓
	225/55R16	99HXL	BLK	7.0	233	680	340/50	✓
17	205/45R17	88VXL	BLK	7.0	206	616	340/50	✓
	205/50R17	93VXL	BLK	6.5	214	638	340/50	✓
	205/55R17	95VXL	BLK	6.5	214	658	340/50	✓
	215/45R17	91VXL	BLK	7.5	213	626	340/50	✓
	215/50R17	95VXL	BLK	7.5	226	648	340/50	✓
	215/55R17	98VXL	BLK	7.0	226	668	340/50	✓
	225/45R17	94VXL	BLK	7.5	225	634	340/50	✓
	225/50R17	98VXL	BLK	8.0	233	658	340/50	✓
	225/55R17	101VXL	BLK	7.0	233	680	340/50	✓
	235/45R17	97VXL	BLK	7.5	236	644	340/50	✓
	235/55R17	103VXL	BLK	7.5	245	690	340/50	✓
	245/45R17	99VXL	BLK	8.0	243	652	340/50	✓
18	215/45R18	93VXL	BLK	7.0	213	651	340/50	✓
	215/55R18	99VXL	BLK	7.0	224	693	340/50	✓
	225/40R18	92VXL	BLK	8.0	234	637	340/50	✓
	225/45R18	95VXL	BLK	7.5	225	659	340/50	✓
	225/50R18	99VXL	BLK	7.0	233	683	340/50	✓
	225/55R18	102VXL	BLK	7.0	233	705	340/50	✓
	225/60R18	104HXL	BLK	6.5	228	727	340/50	✓
	235/45R18	98VXL	BLK	8.0	240	667	340/50	✓
	235/50R18	101VXL	BLK	7.5	243	693	340/50	✓
	235/55R18	104VXL	BLK	7.5	245	715	340/50	✓
	235/60R18	107HXL	BLK	7.0	240	739	340/50	✓
	245/40R18	97VXL	BLK	8.5	248	653	340/50	✓
	245/45R18	100VXL	BLK	8.0	243	677	340/50	✓
	245/60R18	105H	BLK	7.0	248	751	300/44	✓

Wheel Diameter	Size Description		Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
18	255/40R18	99VXL	BLK	9.0	263	661	340/50	✓
	255/45R18	103VXL	BLK	8.5	257	687	340/50	✓
	255/55R18	109VXL	BLK	8.0	265	737	340/50	✓
	255/60R18	112HXL	BLK	7.5	257	763	340/50	✓
	265/60R18	114HXL	BLK	8.0	272	775	340/50	✓
	285/60R18	120HXL	BLK	8.5	290	802	340/50	✓
19	225/40R19	93VXL	BLK	8.0	230	663	340/50	✓
	225/45R19	96VXL	BLK	7.5	225	685	340/50	✓
	225/55R19	103VXL	BLK	7.0	233	731	340/50	✓
	235/35R19	91VXL	BLK	8.5	241	647	340/50	✓
	235/45R19	99VXL	BLK	8.0	236	669	340/50	✓
	235/55R19	105VXL	BLK	7.5	245	741	340/50	✓
	245/40R19	98VXL	BLK	8.5	248	679	340/50	✓
	245/45R19	102VXL	BLK	8.0	243	703	340/50	✓
	245/55R19	107VXL	BLK	7.5	253	753	340/50	✓
	255/35R19	96VXL	BLK	9.0	260	661	340/50	✓
	255/40R19	100VXL	BLK	9.0	260	687	340/50	✓
	255/50R19	107VXL	BLK	8.0	265	738	340/50	✓
	255/55R19	111VXL	BLK	8.0	265	763	340/50	✓
	285/45R19	111VXL	BLK	9.5	292	742	340/50	✓
	245/45R20	103VXL	BLK	8.0	243	728	340/50	✓
20	255/45R20	105VXL	BLK	8.5	255	738	340/50	✓
	255/50R20	109VXL	BLK	8.0	265	764	340/50	✓
	255/55R20	110VXL	BLK	8.0	260	789	340/50	✓
	275/40R20	106VXL	BLK	9.5	278	728	340/50	✓
	275/45R20	110VXL	BLK	9.0	273	756	340/50	✓
	275/55R20	117VXL	BLK	8.5	284	810	340/50	✓
	275/60R20	119VXL	BLK	8.0	279	838	340/50	✓
	285/50R20	116VXL	BLK	9.0	297	794	340/50	✓
	315/35R20	110VXL	BLK	11.0	320	728	340/50	✓




WINTER COMMERCIAL
VAN

RANGE: 14-16 ASPECT RATIO: 65-80
SPEED RATE: R SECTION WIDTH: 175-235

SNOWBLAZER
MAX



SNOWBLAZER MAX



Employing a central longitudinal stability channel with dual-width Z-shaped circumferential structural units to maximize snow traction, while optimizing braking distance parameters and significantly enhancing driving stability coefficients on extremely cold surfaces.



Utilizing AI computer-simulated optimized wide-area rolling contact surface design for precise ground pressure distribution control. The innovative shoulder drainage network system effectively blocks water film formation, providing superior wet surface adhesion with efficient snow evacuation capabilities.



Featuring biomimetic block-style tread matrix architecture through precisely calculated rigidity distribution networks, combined with strategically positioned Z-shaped tangential stability elements, delivering multi-dimensional traction vectors on composite ice and snow surfaces under high-load conditions to ensure handling stability.



Equipped with next-generation low-temperature composite materials that maintain optimal molecular chain activity in sub-zero environments, significantly enhancing dynamic adhesion coefficients in winter road conditions while reducing rolling resistance to optimize energy efficiency.



Wheel Diameter	Size Description	Sidewall	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	M+S
14	175/65R14C 90/88R	BLK	5.0	177	584	375/54	✓
	175/70R14C 95/93R	BLK	5.0	177	602	375/54	✓
	175R14C 99/98R	BLK	5.0	178	634	450/65	✓
	185R14C 102/100R	BLK	5.5	188	650	450/65	✓
15	195/70R15C 104/102R	BLK	6.0	201	655	450/65	✓
	215/65R15C 104/102R	BLK	6.5	221	661	450/65	✓
	215/70R15C 109/107R	BLK	6.5	221	683	450/65	✓
	225/70R15C 112/110R	BLK	6.5	228	697	450/65	✓
16	185/75R16C 104/102R	BLK	5.0	184	684	475/69	✓
	195/65R16C 104/102R	BLK	6.0	201	660	475/69	✓
	195/75R16C 107/105R	BLK	5.5	196	698	475/69	✓
	205/65R16C 107/105R	BLK	6.0	209	672	475/69	✓
	215/65R16C 109/107R	BLK	6.5	221	686	475/69	✓
	215/75R16C 113/111R	BLK	6.0	216	728	475/69	✓
	225/65R16C 112/110R	BLK	6.5	228	698	475/69	✓
	235/65R16C 115/113R	BLK	7.0	240	712	475/69	✓





WWW.LANDSPIDERTIRE.COM | QINGDAO LANDSPIDER TIRE CORP.,LTD

The logo for Autocruze, featuring a stylized bird or wing icon in blue and red to the left of the word "AUTOCRUZE" in a bold, black, sans-serif font.

AUTO