



ENJOY YOUR TRIPS WITH WNDFORCE TYRES









WINDFORCE brand was established in 2012, through unremitting team efforts and innovation, WINDFORCE has developed over 1200 tire sizes covering PCR, UHP, SUV, 4X4, VAN, WINTER, ALL SEASON, as well as RACING TYRES.

WINDFORCE brand also has over 120 sizes for its TBR TYRES with full ranges covering steer, drive, trailer and all position wheel.

In line with the vision of "building a professional tire brand", WINDFORCE has obtained various certificates including ISO9001, China CCC, US DOT, EU E-MARK, EU Regulation 117, Saudi Arabia SASO, Nigeria SONCAP, Uruguay LATU, India BIS, Brazil INMENTRO, etc....

With the spirit of customer first, WINDFORCE has become a reliable brand focusing on quality products, and will continuously enhance its excellent services to all partners by our dedicated sales team.

No adventure without risk, no driving without safeguarding. On the way to the future, WINDFORCE TYRE is always around you.









WA1060 (05)

WA1062+(06)





WD2000 (10)

WD2020 (11)



WD2062 (15)

WD2088 (20)



WD2062+(16)

WD2066 (17)







WD3080 (21)

WD3082 (22)





WT3020 (24) WT3000 (23)

WT3030 (25)





WA1066 07







WD2040 (12)





WD2048 (13)



















WHI000





0 - <mark>000</mark>-○ Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

- Application: Trailer Wheel for long distance, also can be used on Steer Wheel.
- Suitable for high speed on good road surface application, with excellent anti-wet property and side-slip resistance.
- Longer mileage, Lower noise, Lower rolling resistance.



ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
H1000R01	11R22.5 148/145M	16	13.0 16.4	8.25	TL	Trailer	Highway	-	-	-	-
H1000R06	295/75R22.5 146/143M	16	11.0 14.0	9.00	TL	Trailer	Highway	-	-	-	-
H1000R04	11R24.5 149/146M	16	11.0 14.0	8.25	TL	Trailer	Highway	-	-	-	-
H1000R11	285/75R24.5 147/144M	16	11.0 14.0	8.25	TL	Trailer	Highway	-	-	-	-
H1000R07	295/80R22.5 152/149M	18	14.5 18.4	9.00	TL	Trailer	Highway	-	-	-	-
H1000R09	315/80R22.5 156/150M	20	14.5 18.4	9.00	TL	Trailer	Highway	-	-	-	-
H1000R08	12R22.5 152/149M	18	14.5 18.4	9.00	TL	Trailer	Highway	-	-	-	-



WHI020



- Application: Steer Wheel for long distance, also can be used on Trailer Wheel.
- Suitable for high speed on good road surface application, with excellent durability, anti-side wear performance.
- Longer mileage, Lower noise, Good stone-picking prevention.

m+S 175-24.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
H1020R02	215/75R17.5 127/124M	16	12.0 15.0	6.00	TL	All	Highway	E	С	В	73
H1020R28	215/75R17.5 135/133J	18	12.0 15.0	6.00	TL	All	Highway	E	С	В	73
H1020R04	235/75R17.5 132/130M	16	12.5 15.8	6.75	TL	All	Highway	E	С	В	73
H1020R29	235/75R17.5 143/141J	18	12.5 15.8	6.75	TL	All	Highway	E	С	В	73
H1020R06	225/70R19.5 128/126M	14	12.5 15.5	6.75	TL	All	Highway	E	С	В	73
H1020R07	245/70R19.5 136/134M	16	12.5 15.8	7.50	TL	All	Highway	E	С	В	73
H1020R08	265/70R19.5 140/138M	16	12.5 15.8	7.50	TL	All	Highway	E	С	В	73
H1020R09	285/70R19.5 146/144M	16	13.0 16.0	8.25	TL	All	Highway	-	-	-	-
H1020R30	285/70R19.5 150/148J	18	13.0 16.0	8.25	TL	All	Highway	E	С	В	73
H1020R25	11R22.5 148/145M	16	14.5 18.4	8.25	TL	All	Highway	D	С	В	73
H1020R14	295/75R22.5 146/143M	16	15.5 19.6	9.00	TL	All	Highway	D	С	В	73
H1020R22	11R24.5 149/146M	16	14.5 18.4	8.25	TL	All	Highway	D	С	В	73
H1020R24	285/75R24.5 147/144M	16	15.5 19.6	8.25	TL	All	Highway	-	-	-	-
H1020R01	255/70R22.5 140/137M	16	13.0 16.0	7.50	TL	All	Highway	-	-	-	-
H1020R10	275/70R22.5 148/145M	16	14.5 18.4	8.25	TL	All	Highway	E	С	В	73
H1020R15	295/80R22.5 152/149M	18	15.5 19.6	9.00	TL	All	Highway	D	С	В	73
H1020R17	315/70R22.5 154/150M	20	15.0 19.0	9.00	TL	All	Highway	D	С	В	73
H1020R18	315/80R22.5 156/150M	20	15.5 19.6	9.00	TL	All	Highway	D	С	В	73
H1020R16	12R22.5 152/149M	18	15.5 19.6	9.00	TL	All	Highway	D	С	В	73
H1020R19	385/55R22.5 160L	20	15.5 19.6	12.25	TL	All	Highway	С	С	В	73
H1020R20	385/65R22.5 160L	20	15.5 19.6	11.75	TL	All	Highway	С	С	В	73



0

Trailer Wheel.

○ Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

excellent durability, anti-side wear performance.

• Application: Steer Wheel for long distance, also can be used on

• Suitable for high speed on good road surface application, with

• Longer mileage, Lower noise, Good stone-picking prevention.







- Standard Wheel Permitted Wheel Prohibited Wheel
- Application: Steer Wheel for long distance, also can be used as All Position pattern.
- New designed pattern, Suitable for well paved road condition with high speed level and excellent durability.
- Heavy loading capacity, Low heat build-up, High speed and Low noise.

M+S 22.5 INCH

ltem	Sizes	Ply	Tread Depth	Standard	Tubeless/	Rim	Application				dB
No.	Description	Rating	MM 1/32"	Rim	Tube	position			2002	M ABC	ue
H3060R10	12R22.5 152/149M	18	15.0 19.0	9.00	TL	All	Highway	-	-	-	-
H3060R11	295/60R22.5 150/147M	18	15.0 19.0	9.00	TL	All	Highway	D	С	В	72
H3060R12	295/80R22.5 152/149M	18	15.5 19.6	9.00	TL	All	Highway	D	С	В	72
H3060R13	315/80R22.5 157/154M	20	15.0 19.0	9.00	TL	All	Highway	D	С	В	72

m+S 1*7S*-*22.5 INCH*

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
H1022R01	315/80R22.5 156/150M	20	15.0 19.0	9.00	TL	All	Highway	-	-	-	-
H1022R03	12R22.5 152/149L	18	15.0 19.0	9.00	TL	All	Highway	-	-	-	-
H1022R02	9.5R17.5 143/141J	18	13.0 16.4	6.75	TL	All	Highway	-	-	-	-





n w

WA1060

• Standard Wheel • Permitted Wheel • Prohibited Wheel

• Application: All Position Wheels for On/Off use.

poor road condition with sideslip resistance.

• Mixed pattern, Suitable for mixed road surface and relatively

• Excellent crack & tear resistance, High speed, Long mileage.



WA1062+



- Application: All Position Wheels for long mileage load series.
- New designed pattern, Suitable for well paved road condition with excellent durability.
- Standard load, Low heat build-up, High speed.

M+S 24 INCH

ltem	Sizes	Ply	Tread Depth	Sta
No.	Description	Rating	MM 1/32"	F
A1062R01+	12.00R24 160/157K	20	16.0 20.8	



M+S 16-24.5 INCH

ltem No.	Size Descrip	-	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
A1060R15	7.00R16LT	118/114L	14	12.0 15.0	5.50	TT	All	On/Off	-	-	-	-
A1060R13	7.50R16LT	122/118L	14	13.0 16.4	6.50	TT	All	On/Off	E	E	В	73
A1060R14	8.25R16LT	128/124K	16	13.0 16.4	6.50	TT	All	On/Off	E	E	В	73
A1060R06	9.00R20	144/142K	16	15.5 19.6	7.00	TT	All	On/Off	D	С	В	73
A1060R07	10.00R20	149/146K	18	16.0 20.2	7.50	TT	All	On/Off	D	С	В	73
A1060R08	11.00R20	150/147K	18	16.0 20.2	8.00	TT	All	On/Off	D	С	В	73
A1060R09	12.00R20	156/153K	20	16.0 20.2	8.50	TT	All	On/Off	D	С	В	73
A1060R10	12.00R24	160/157K	20	15.0 20.2	8.50	TT	All	On/Off	D	С	В	73
A1060R01	11R22.5	148/145M	16	14.5 18.4	8.25	TL	All	On/Off	D	С	В	73
A1060R02	11R24.5	149/146M	16	14.5 18.4	8.25	TL	All	On/Off	D	С	В	73
A1060R11	295/80R22.5	152/149M	18	15.0 19.0	9.00	TL	All	On/Off	С	С	В	73
A1060R04	315/80R22.5	156/150M	20	15.0 19.0	9.00	TL	All	On/Off	С	С	В	73
A1060R03	12R22.5	152/149M	18	15.0 19.0	9.00	TL	All	On/Off	С	С	В	73
A1060R05	13R22.5	156/150L	20	15.0 19.0	9.75	TL	All	On/Off	С	С	В	73



ndard im	Tubeless/ Tube	Rim position	Application				dB
50	TT	All	On/Off	-	-	-	-

HEAVY TRUCK

6

WAI066

○ Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

• Application: All Position Wheels for On/Off use.

poor road condition with high loading capability.

• Mixed pattern, Suitable for mixed road surface and relatively

• Excellent crack & tear resistance, Good anti-uneven wear



WAI068



- Application: All Position Wheels for long mileage load series.
- New designed pattern, Suitable for well paved road condition with excellent durability.
- Standard load, Low heat build-up, High speed.

M+S 20 INCH

character.

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
A1066R03	9.00R20 144/142K	16	15.5 19.6	7.00	TT	All	On/Off	-	-	-	-
A1066R04	10.00R20 149/146K	18	16.0 20.2	7.50	TT	All	On/Off	-	-	-	-
A1066R01	11.00R20 152/149K	18	16.0 20.2	8.00	TT	All	On/Off	-	-	-	-
A1066R02	12.00R20 156/153K	20	16.0 20.2	8.50	TT	All	On/Off	-	-	-	-

M+S 24 INCH

ltem No.	Sizes Description		Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
A1068R01	12.00R24 160/157K	20	16.0 20.2	8.50	TT	All	On/Off	E	С	В	73







HEAVY TRUCK

8

WAI088



WD2000



- Application: Steer Wheel for long distance, also can be used as Trailer Wheel pattern.
- New designed pattern, Suitable for well paved road condition with high speed level and excellent durability.
- Heavy loading capacity, Low heat build-up, High speed and Low noise.



- Application: Drive Wheel for medium mileage loading series.
- Close Shoulder designs, the block pattern offer excellent drive force and good braking performance on paved road condition.
- Excellent load capability, Longer mileage, Super Durability.

M+S 20 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB	
A1088R01	11.00R20 152/149K	18	16.5 20.8	8.00	TT	All	Highway	-	-	-	-	

M+S 22.5-24.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2000R02	11R22.5 148/145M	16	20.0 25.2	8.25	TL	Drive	Highway	-	-	-	-
D2000R06	295/75R22.5 146/143K	16	20.0 25.2	9.00	TL	Drive	Highway	-	-	-	-
D2000R04	11R24.5 149/146K	16	20.0 25.2	8.25	TL	Drive	Highway	-	-	-	-
D2000R08	285/75R24.5 147/144L	16	20.0 25.2	8.25	TL	Drive	Highway	-	-	-	-







HEAVY TRUCK 10

WD2020



- Application: Drive Wheel for medium mileage load series.
- Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Excellent load capability, Longer mileage, Super Durability.



WDZ040



- Application: Drive Wheel for short distance on/off road use.
- Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- Longer Mileage, Strong Structure, Good anti-wear performance.

m+S 1*7S*-*2*4*.S INCH*

ltem No.	Sizes Descript		Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2020R27	9.5R17.5	131/129L	16	15.0 19.0	6.75	TL	Drive	Highway	-	-	-	-
D2020R02	215/75R17.5	127/124M	16	15.0 19.0	6.00	TL	Drive	Highway	E	С	В	75
D2020R04	235/75R17.5	132/130M	16	15.5 19.6	6.75	TL	Drive	Highway	E	С	В	75
D2020R28	235/75R17.5	143/141J	18	15.5 19.6	6.75	TL	Drive	Highway	E	С	В	75
D2020R06	225/70R19.5	128/126M	14	15.5 19.6	6.75	TL	Drive	Highway	E	С	В	75
D2020R07	245/70R19.5	136/134M	16	15.5 19.6	7.50	TL	Drive	Highway	E	С	В	75
D2020R08	265/70R19.5	140/138M	16	15.5 19.6	7.50	TL	Drive	Highway	E	С	В	75
D2020R29	265/70R19.5	143/141J	18	15.5 19.6	7.50	TL	Drive	Highway	E	С	В	75
D2020T09	285/70R19.5	146/144M	16	16.0 20.0	8.25	TL	Drive	Highway	E	С	В	75
D2020R12	11R22.5	148/145M	16	20.0 25.2	8.25	TL	Drive	Highway	E	С	В	75
D2020R22	11R24.5	149/146K	16	20.0 25.2	8.25	TL	Drive	Highway	E	В	В	75
D2020R10	275/70R22.5	148/145M	16	18.0 22.8	8.25	TL	Drive	Highway	E	С	В	75
D2020R15	295/80R22.5	152/149M	18	20.0 25.2	9.00	TL	Drive	Highway	E	В	В	75
D2020R17	315/70R22.5	154/150M	20	20.0 25.2	9.00	TL	Drive	Highway	E	В	В	75
D2020R18	315/80R22.5	156/150M	20	20.0 25.2	9.00	TL	Drive	Highway	E	В	В	75
D2020R16	12R22.5	152/149K	18	20.0 25.2	9.00	TL	Drive	Highway	E	С	В	75
D2020R20	10.00R20	149/146K	18	20.0 25.2	7.50	TT	Drive	Highway	E	В	В	75

M+S 20 INCH

ltem	Sizes	Ply	Tread Depth	Sta
No.	Description	Rating	MM 1/32"	F
D2040R01	10.00R20 149/146K	18	20.0 25.2	





ndard Rim	Tubeless/ Tube	Rim position	Application				dB	
.50	TT	Drive	On/Off	-	-	-	-	

HEAVY TRUCK 12





- Application: Drive Wheel for short distance on/off road use.
- Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- Longer Mileage, Strong Structure, Good anti-wear performance.



WD2060



- Application: Drive Wheel for On/Off Road use.
- Suitable for mix road use and relatively poor road condition with excellent traction character.
- Excellent load capability, Longer mileage, Good anti-wearing.

M+S 22.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2048R02	315/80R22.5 156/150K	20	18.0 22.8	9.00	TL	Drive	On/Off	-	-	-	-
D2048R01	12R22.5 152/149K	18	20.0 25.2	9.00	TL	Drive	On/Off	-	-	-	-

M+S 22.5-24.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2060R01	11R22.5 148/145M	16	20.0 25.2	6.00	TL	Drive	On/Off	D	С	А	73
D2060R06	11R24.5 149/146K	16	20.0 25.2	6.75	TL	Drive	On/Off	D	С	А	73
D2060R02	295/80R22.5 152/149L	18	20.0 25.2	6.00	TL	Drive	On/Off	D	В	А	73
D2060R04	315/80R22.5 156/150K	20	20.0 25.2	6.75	TL	Drive	On/Off	D	В	А	73
D2060R03	12R22.5 152/149K	18	20.0 25.2	6.75	TL	Drive	On/Off	D	В	А	73
D2060R05	13R22.5 156/150K	20	20.0 25.2	7.50	TL	Drive	On/Off	D	В	А	73







HEAVY TRUCK 14





- Application: Drive Wheel for medium mileage load series.
- Open Sahoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Excellent load capability, Longer mileage, Super Durability.



WD2062+



- Application: Drive Wheel for medium mileage load series.
- Open Sahoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Excellent load capability, Longer mileage, Super Durability.

M+S 16-20 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
	1	0					0=10ff				
D2062R07	7.00R16LT 118/114K	14	14.5 18.4	5.50	TT	Drive	On/Off	-	-	-	-
D2062R05	7.50R16LT 122/118K	14	14.5 18.4	6.50	TT	Drive	On/Off	-	-	-	-
D2062R06	8.25R16LT 128/124K	16	14.5 18.4	6.50	TT	Drive	On/Off	-	-	-	-
D2062R01	9.00R20 144/142K	16	18.0 22.8	7.00	TT	Drive	On/Off	-	-	-	-
D2062R02	10.00R20 149/146K	18	18.0 22.8	7.50	TT	Drive	On/Off	-	-	-	-

m+s 20 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2062R03+	11.00R20 152/149K	18	18.5 23.4	8.00	TT	Drive	On/Off	-	-	-	-
D2060R04+	12.00R20 156/153K	20	19.5 24.6	8.50	TT	Drive	On/Off	-	-	-	-









HEAVY TRUCK 16

WD2066



○ Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

- Application: Drive Wheel for short distance on/off road use.
- Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- Longer Mileage, Strong Structure, Good anti-wear performance.



WD2068



- Application: Drive Wheel for short distance on/off road use.
- Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- Longer Mileage, Strong Structure, Good anti-wear performance.

m+S 20 INCH

ltem No.	Sizes Description	Ply Rating	mede beptin	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2066R01	11.00R20 152/149J	18	18.5 23.4	8.00	TT	Drive	On/Off	-	-	-	-
D2066R02	12.00R20 156/153J	20	19.5 24.6	8.50	TT	Drive	On/Off	-	-	-	-

m+s 24 INCH

ltem	Sizes	Ply	Tread Depth	Star
No.	Description	Rating	MM 1/32"	R
D2068R01	12.00R24 160/157K	20	16.0 20.8	







ndard Rim	Tubeless/ Tube	Rim position	Application				dB	
.50	TT	Drive	On/Off	-	-	-	-	

HEAVY TRUCK 18

WD2080



• Application: Steer and Drive Wheel for on/off road use.

- Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- Longer Mileage, Strong Structure, Good anti-wear performance.



WDZ088



○ Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

- Application: Drive Wheel for short distance on/off road use.
- Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.
- Longer Mileage, Strong Structure, Good anti-wear performance.

m+s 20 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2080R01	9.00R20 144/142G	16	20.0 25.2	7.0	TT	Drive	On/Off	-	-	-	-
D2080R02	10.00R20 149/146G	18	20.0 25.2	7.5	TT	Drive	On/Off	-	-	-	-
D2080R03	11.00R20 152/149G	18	21.0 26.5	8.0	TT	Drive	On/Off	-	-	-	-
D2080R04	12.00R20 156/153G	20	21.0 26.5	8.5	TT	Drive	On/Off	-	-	-	-



M+S 20-24 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D2088R01	11.00R20 152/149G	18	21.0 26.4	8.00	TT	Drive	Off	-	-	-	-
D2088R02	12.00R20 156/153G	20	22.0 27.8	8.50	TT	Drive	Off	-	-	-	-
D2088R03	12.00R24 160/157K	20	22.0 27.8	8.50	TT	Drive	Off	-	-	-	-
D2088R04	11R22.5 146/143K	16	22.0 27.8	8.25	TL	Drive	Off	-	-	-	-
D2088R06	295/80R22.5 152/149K	18	22.0 27.8	9.00	TL	Drive	Off	-	-	-	-
D2088R08	12R22.5 152/149K	18	22.0 27.8	9.00	TL	Drive	Off	-	-	-	-
D2088R09	13R22.5 156/150K	20	22.0 27.8	9.75	TL	Drive	Off	-	-	-	-







- Application: Drive Wheel for medium mileage load series.
- Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Excellent load capability, Longer mileage, Super Durability.





- Application: Drive Wheel for medium mileage load series.
- Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Excellent load capability, Longer mileage, Super Durability.

m+s 22.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D3080R10	12R22.5 152/149M	18	20.0 25.2	9.00	TL	Drive	Highway	-	-	-	-
D3080R11	295/60R22.5 150/147M	18	20.0 25.2	9.00	TL	Drive	Highway	D	С	В	74
D3080R12	295/80R22.5 152/149M	18	20.0 25.2	9.00	TL	Drive	Highway	-	-	-	-
D3080R13	315/80R22.5 157/154M	20	20.0 25.2	9.00	TL	Drive	Highway	D	С	В	74

m+s 22.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
D3082R01	315/80R22.5 157/154M	20	22.0 27.8	9.00	TL	Drive	Highway	E	С	В	75





HEAVY TRUCK 22

WT3000



- Application: Trailer Wheel for regional use.
- Suitable for high and medium speed on good road surface with excellent anti- skid-side character and drainage performance.
- Excellent loading capacity, Low rolling resistance, Low noise.



WT3020



○ Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

- Application: Trailer Wheel for regional use.
- Suitable for high speed on paved road surface with excellent anti-skid-side character and durability performance.
- Excellent loading capacity, Low rolling resistance, Low noise.

M+S ZZ.S INCH

ltem No.	Sizes Description	-	Tread Depth MM 1/32"	Sta I
T3020R01	385/65R22.5 160L	20	15.5 19.6	1



m+S 175-22.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
T3000R01	215/75R17.5 135/133J	18	12.0 15.0	6.00	TL	Trailer	Highway	E	С	В	73
T3000R02	235/75R17.5 143/141J	18	12.5 15.8	6.75	TL	Trailer	Highway	E	С	В	73
T3000R03	225/70R19.5 128/126M	14	12.5 15.8	6.75	TL	Trailer	Highway	E	С	В	73
T3000R04	245/70R19.5 136/134M	16	12.5 15.8	7.50	TL	Trailer	Highway	E	С	В	73
T3000R05	265/70R19.5 143/141J	18	12.5 15.8	7.50	TL	Trailer	Highway	E	С	В	73
T3000R06	285/70R19.5 150/148J	18	13.0 16.0	8.25	TL	Trailer	Highway	E	С	В	73
T3000R07	275/70R22.5 148/145M	16	14.5 18.4	8.25	TL	Trailer	Highway	E	С	В	73
T3000R08	385/55R22.5 160L	20	15.5 19.6	12.25	TL	Trailer	Highway	С	С	В	73
T3000R09	385/65R22.5 160L	20	15.5 19.6	11.75	TL	Trailer	Highway	С	С	В	73
T3000R11	445/65R22.5 169K	20	16.0 20.2	13.00	TL	Trailer	Highway	С	С	В	73



tandard
Rim
Rim
TubeTube
positionRim
ApplicationApplicationImage: Comparison
ComparisonImage: Comparison
Compari

HEAVY TRUCK 24

WT3030



WT5000



○ Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

- Application: Drive Wheel for On/Off Road use.
- Suitable for mix road use and relatively poor road condition with excellent traction character.
- Excellent load capability, Longer mileage, Good antiwearing.



O Standard Wheel ○ Permitted Wheel ⑧ Prohibited Wheel

- Application: Trailer Wheel for regional use.
- Suitable for high speed on paved road surface with excellent anti-skid-side character and durability performance.
- Excellent loading capacity, Low rolling resistance, Low noise.

M+S 22.5 INCH

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
T3030R02	385/65R22.5 160L	20	16.0 20.2	11.75	TL	All	On/Off	С	В	В	73
T3030R04	445/65R22.5 169K	20	16.0 20.2	13.00	TL	All	On/Off	С	В	В	74

*m***+S** 22.5 INCH

ltem	Sizes	Ply	Tread Depth	Sta
No.	Description	Rating	MM 1/32"	R
T5000R01	385/65R22.5 164K	24	15.0 18.9	







ndard lim	Tubeless/ Tube	Rim position	Application				dB	
75	TL		Highway	-	-	-	-	

HEAVY TRUCK 26

WT5050

TBR CERTIFICATES



- Application: Trailer Wheel for long distance Road use.
- Suitable for mix road use and relatively poor road condition with excellent traction character.
- Excellent load capability, Longer mileage, Good antiwearing.



*m***+S 22.5 INCH**

ltem No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				dB
T5050R01	385/65R22.5 164K	24	17.0 21.4	11.75	TL	All	On/Off	-	-	-	-



SMART	-WAY
Martin Santa Bandanatar Bandi Can Adam Martin Santa Mil - 1 III Martin Martina	Yuglid In-soling missane rises may be instilled on all and positions of the taxon A list instance by popping shared a counting to be manchemen's specifications. Instances in the total share all shared and shared total shared to the shared based shared and the total based on the shared shared total shared to the shared based above a parameters instances dependent shared and the shared shared based above a shared based on the shared shared based on the shared based on the shared have a shared based on the shared shared based on the shared based on the shared have the shared based on the shared shared based on the shared based on the shared have the shared based on the shared based on the shared based on the shared based have the shared based on the shared based on the shared based on the shared based have the shared based on the shared based on the shared based on the shared based have the shared based on the shared based have the shared based on th
N: Ear Wag The Star Star Star Star Star Star Star Star	<text><text><text><text></text></text></text></text>
Approved Mandrig Fander (2014). Ltd. The David and Mark With the Constant INVECTOR STATE INVECTOR STATE The Mark With The Mark Mark Mark Mark The Mark Mark Mark Mark Mark Mark The Mark Mark Mark Mark Mark Mark Mark The Mark Mark Mark Mark Mark Mark Mark Mark	

С	ertificate				
Energy	Efficiency Label			4363-790 Saudi Sta	ng thatle criticity all trap much that it dants, Metrology and Quality Org.
e Saudi S	Standards, Metrology and	Quality Org. (S	ASO)		
s certified :	SHANDONG HAOHUA TIP	RE CO., LTD		following pr	oduct:
		Tire Specs	RR Grade	WG Grade	Licence Number
			nn Glade	110 01908	Livence Number
The Product	Manufacturer & Commercial Name	ine option			
The Product		315/80 R22.5 C3 156 K	Average	Good	TR012229421







Ansate Ansate Ansate Ansate	Anna Anna Anna Anna Anna Anna Anna Anna	Anna Anna Anna Anna Anna Anna Anna Anna	Anna Anna Anna Anna Anna Anna Anna Anna	Here and the set of th	Santala K Santala
Barry Barry <th< td=""><td>Barry Line Barry L</td><td>Barry Line Barry L</td><td>Barry Line Barry L</td><td>Hang et al. (1997) Hang e</td><td>x ingt 28 Regresentation Trands Law Job 4045 4045 Formed Co 40</td></th<>	Barry Line Barry L	Barry Line Barry L	Barry Line Barry L	Hang et al. (1997) Hang e	x ingt 28 Regresentation Trands Law Job 4045 4045 Formed Co 40
Marting And Marchard Andrey Networks Andrew Marchard Andrey Networks Andrew Marchard Andrey Networks Andrew Marchard Andrew Networks Andrew Networks Andrew Marchard Andrew Networks Andrew M	Markar Andrewska refererer Markar Markar Markar Markar Markar<	Markar Andrewska refererer Markar Markar Markar Markar Markar<	Markar Andrewska refererer Markar Markar Markar Markar Markar<	Mathem All Instructure of the years and the years and the years Margin was financial was been was financial was financial was financial was financial was financial was financi	201 20 20 20 20 20 20 20 20 20 20 20 20 20
Normal Normal Normal Normal International 1000 1000 1000 1000 International 1000 1000 1000 1000 1000 International 1000	Normal Normal Normal Normal Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Contract Normal Contract Cont <td>Normal Normal Normal Normal Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Contract Normal Contract Cont<td>Normal Normal Normal Normal Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Contract Normal Contract Cont<td>International Control of the Internation of Control of</td><td>28 Nagreenshin Traik LW 304 0.20 1047 N445 47 Facesed G Wel 48.3 con</td></td></td>	Normal Normal Normal Normal Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Contract Normal Contract Cont <td>Normal Normal Normal Normal Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Contract Normal Contract Cont<td>International Control of the Internation of Control of</td><td>28 Nagreenshin Traik LW 304 0.20 1047 N445 47 Facesed G Wel 48.3 con</td></td>	Normal Normal Normal Normal Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Normal Contract Contract Contract Contract Contract Contract Normal Contract Cont <td>International Control of the Internation of Control of</td> <td>28 Nagreenshin Traik LW 304 0.20 1047 N445 47 Facesed G Wel 48.3 con</td>	International Control of the Internation of Control of	28 Nagreenshin Traik LW 304 0.20 1047 N445 47 Facesed G Wel 48.3 con
Marcine Construint Marcine	Marcine State	Marcine State	Marcine State	Marcine All set of the set	Represente Track Las Met- 0.3: Met- 0.3: Met- e 2.5: Second 0.5: Met- Met- Met- Met- Met- Met- Met- Met-
Margin Application Application Margin Margin Margin Margin Margin Margin Margin Margin <td>Markan Sangarang Markan Sangarang<</td> <td>Markan Sangarang Markan Sangarang<</td> <td>Markan Sangarang Markan Sangarang<</td> <td>Marcine All set of the set</td> <td>Tradit Like 304 0.5 10427 N405 1 47 7 7 805 47 8 8 9 4 3 4 4 3 4 5 3 4 5 4 5 4 5 4 5 4 5 4 5</td>	Markan Sangarang Markan Sangarang<	Markan Sangarang Markan Sangarang<	Markan Sangarang Markan Sangarang<	Marcine All set of the set	Tradit Like 304 0.5 10427 N405 1 47 7 7 805 47 8 8 9 4 3 4 4 3 4 5 3 4 5 4 5 4 5 4 5 4 5 4 5
Answire Answire <t< td=""><td>Annue Antonio Indonesia (Marcine) (M</td><td>Annue Antonio Indonesia (Marcine) (M</td><td>Annue Antonio Indonesia (Marcine) (M</td><td>District Bolds Bolds</td><td>Lin 104 0.5: 1047 1045 07 7 mmd 0 104 104 104 104 104 104 104</td></t<>	Annue Antonio Indonesia (Marcine) (M	Annue Antonio Indonesia (Marcine) (M	Annue Antonio Indonesia (Marcine) (M	District Bolds	Lin 104 0.5: 1047 1045 07 7 mmd 0 104 104 104 104 104 104 104
Marcina 44.4 No. Substance (M) (S) 4.8 40.5 Marcina Marcina Marcina Marcina Marcina Marcina Marcina Marcina Marcina Marcina Marcina	Instrume 64.24 No. Solutionum (M.) 6.9 M J. Image: Solutionum (M.) Solutionum (M.) Solutionum (M.) Image: Solutionum	Instrume 64.24 No. Solutionum (M.) 6.9 M J. Image: Solutionum (M.) Solutionum (M.) Solutionum (M.) Image: Solutionum	Instrume 64.24 No. Solutionum (M.) 6.9 M J. Image: Solutionum (M.) Solutionum (M.) Solutionum (M.) Image: Solutionum	Instrume 441,44 Yes Descriptions 812, Mark Server, S	0.3:1947 Hold : Hold : Paradel Q W-4 H.3:
Image: Section (Section (Bit of the sector of	Bit of the sector of	Bit of the sector of	Banag hergy () Banag he	Ness
Banagi Kang Jung Bit Statubanes Unit: Bit Statubane	Image Image <th< td=""><td>Image Image <th< td=""><td>Image Image <th< td=""><td>Heard Bergy Win Deard Berger 105 Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Ser for Associatin</td><td>Ness</td></th<></td></th<></td></th<>	Image Image <th< td=""><td>Image Image <th< td=""><td>Heard Bergy Win Deard Berger 105 Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Ser for Associatin</td><td>Ness</td></th<></td></th<>	Image Image <th< td=""><td>Heard Bergy Win Deard Berger 105 Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Ser for Associatin</td><td>Ness</td></th<>	Heard Bergy Win Deard Berger 105 Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Systems Boyl Ser for Associating Systems Storp Ser for Associating Ser for Associatin	Ness
Image: Section 2014 (Section 2014) (Section	Ali Anima and Anima a	Ali Anima and Anima a	Ali Anima and Anima a	Mat Material rate () and	0 90 90 90 90 90 90 90 90 90 90 90 90 90
44 Anomalysis of a biological state of a biologi	4 Anomalysis of a strain	4 Anomalysis of a strain	4 Anomalysis of a strain	48 Schward varupider to disinkal regulation for extrame of the technological schward regulation Text Data Schward regulation Cathological schward regulation 600 SER 110 600 SER	0 805 96.5
Notes:	Markan Answer Answer<	Markan Answer Answer<	Markan Answer Answer<	Norkinski kar Norkinski Samer	0 805 96.5
Nature 0 Instruct outer quentity, charge and the set outer set outer set to be an experiment. Parallel Parallel Description Parallel Parallel Parallel Description 0.00 EU 0.00 EU 0.00 EU 0.00 E	Nature 620 Testing - tangen and this, manage and this, manage and the second and the	Nature 620 Testing - tangen and this, manage and this, manage and the second and the	Nature 620 Testing - tangen and this, manage and this, manage and the second and the	Balance 40 Interactive for learning entry to below and the product of the sector of t	0 84 84
Company and 2003/03.10 Web Manage Research New Sey Holes (2) 603/03.11 Medie is the school angulation. 44.8 New Sey Holes (2) 603/03.11 Medie is the school and regulation. 44.8	Energy vi 4 03938117 for wei Samp Sampling Sam	Energy vi 4 03938117 for wei Samp Sampling Sam	Energy vi 4 03938117 for wei Samp Sampling Sam	Company of ease tables for the sector of a space of the technologic application Coefficient (HKC) 653-983-117 Andre to the technologic application Here Sing Index (Sp) 653-983-117 Andre to the technologic application	96.5 ····
taking instances GO3 023 117 Advers the technol regulation, 44, 3 + Sec. Sec. Sec. Sec. Sec. Sec. Se	Mang Analasan Mang Mang Mag Nan Grig Juan (20) 653 833 117 Advin the surface at agulation 46,3 km Nan Grig Juan (20) 653 833 117 Advin the surface at agulation 4548 Wang Kegjeng	Mang Analasan Mang Mang Mag Nan Grig Juan (20) 653 833 117 Advin the surface at agulation 46,3 km Nan Grig Juan (20) 653 833 117 Advin the surface at agulation 4548 Wang Kegjeng	Mang Analasan Mang Mang Mag Nan Grig Juan (20) 653 833 117 Advin the surface at agulation 46,3 km Nan Grig Juan (20) 653 833 117 Advin the surface at agulation 4548 Wang Kegjeng	Marke I Mark 6653 8/0 117 Rafker Is the technical regulation. Mark Sing Index (St) 6653 8/0 117 Rafker Is the sectional regulation.	**
Candidant (Mar) 000 80 11 Market in the factorial ingulation. BLA.co. We Sing Market (R) 663 803 11 Markets in a school ingulation. 61.54	Cardinare (May) 603 80 10 March In Konna Angalanan, March - Mar Grighelan (S) 653 803 10 March I An Konna Angalanan, 41.83 Wang Englang	Cardinana (Mar) 603 80 10 Marko II Markova Angalanan, Markova Mar Griginda (S) 653 803 10 Markova Markova Angalanan, 44.83 Wang Englang	Cardinana (Mar) 603 80 10 Marko II Markova Angalanan, Markova Mar Griginda (S) 653 803 10 Markova Markova Angalanan, 44.83 Wang Englang	Caefficien (MC) 400 82 117 Addr 5 the Bochcae Aguitoria. Met Grip Index (S) 650 803 117 Addr 5 the Bochcael aguitation.	
Net Grig Seller (S): 653-853 117 Andre to the solvenus' regulation. 41.84	Net Grig belan (Sp. 653-803 117) Antor to the solvenul regulation. 81.88	Net Grig belan (Sp. 653-803 117) Antor to the solvenul regulation. 81.88	Net Grig belan (Sp. 653-803 117) Antor to the solvenul regulation. 81.88	Ret Grg Index (G) 553 808 117 Keller is the sectorical regulation.	41.42
Warg Regiang	Warg Regiang	Warg Regiang	Warg Regiang		
				Takanga Tukan ka	Ediport

HEAVY TRUCK 28